



BLDC Motor - Chilled Water Cassette – (4 way)

			Eurovent Certified										
Model			MKD-V300	MKD-V400	MKD-V500	MKA-V600R	MKA-V750R	MKA-V850R	MKA-V950R	MKA-V1200R	MKA-V1500R	MKA-V1200RB	MKA-V1500RB
Airflow	(H/M/L)	CMH	560/392/280	717/502/359	785/550/393	1133/793/567	1255/879/628	1441/1009/721	1494/1046/747	1596/1117/798	1850/1295/925	2040/1400/900	2550/1740/1130
Cooling Capacity	(H/M/L)	kW	3.02/2.3/1.75	3.93/3.07/2.48	4.24/3.31/2.67	5.58/4.35/3.52	5.77/4.5/3.63	6.84/5.33/4.30	6.99/5.27/4.16	7.01/5.32/4.34	10.64/8.09/6.60	10.6/8.6/6.1	11.1/9.0/6.5
Power Supply		V/Ph/Hz	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50
Power Input	(H)	W	22.7	27	32	42	50	64	71	91	124	126	190
Noise Level (NC)	(H/M/L)		30/25/17	36/32/24	39/33/26	38/29/22	41/33/24	42/32/24	43/33/27	44/35/28	46/36/29	43/36/25	47/40/34
Indoor Unit Dimensions	WxHxD	mm	575x261x575	575x261x575	575x261x575	840x230x840	840x230x840	840x300x840	840x300x840	840x300x840	840x300x840	950x950x300	950x950x300
Panel Dimensions	WxHxD	mm	647x50x647	647x50x647	647x50x647	950x45x950	950x45x950	950x45x950	950x45x950	950x45x950	950x45x950	1050x55x1050	1050x55x1050